



**fitted with**

- work equipment**
- connected load**
- power consumption**
- system of protection**
- class of protection**
- technology**
- usage**
- luminaire body**
- lamp cover**
- tubular sections**

- balance of articulation joints**
- weight (net)**
- mains lead**

- fastening**
- lens; dimensions**
- lens material**
- lens; diopters**
- add-on lens; dimensions**
- add-on lens; diopters**
- special features**

- LED
- Energy efficiency category A+
- electronic plug-in ballast
- 100-240 V; 50/60 Hz
- approx. 14 W
- IP 20
- II
- multi-stage switchable, continuously dimmable
- multi-function switch
- plastic, untreated, black
- screen, milky, Polyamide
- tubular aluminium section, anodized, aluminium coloured
- anodised
- spring
- approx. 2.7 kg
- approx. 3.4 m; mains plug
- US-ConnectionStandard
- US-ConnectionStandard
- US-ConnectionStandard
- screw-down flange
- Ø 160 mm
- glass
- 3,5
- Ø 31.5 mm
- 8
- adhesive add-on magnifier, long arms, light characteristic can be adjusted with a three-way switch



BS 1363



CEE 7/XVI



NEMA 1-15P

**illuminance**

distance: 15 cm

Em: 4703 lx  
Emax: 7105 lx  
Emin: 1611 lx

