




|   |   |
|---|---|
| <p><b>fitted with</b></p> <p><b>work equipment</b></p> <p><b>connected load</b></p> <p><b>power consumption</b></p> <p><b>luminous flux</b></p> <p><b>luminous efficacy</b></p> <p><b>light distribution</b></p> <p><b>light colour</b></p> <p><b>color rendering index (CRI)</b></p> <p><b>system of protection</b></p> <p><b>class of protection</b></p> <p><b>technology</b></p> <p><b>usage</b></p> <p><b>luminaire body</b></p> <p><b>lamp cover</b></p> <p><b>weight (net)</b></p> <p><b>mains supply</b></p> <p><b>design</b></p> <p><b>fastening</b></p> <p><b>dimension</b></p> <p><b>special features</b></p> | <p>LED</p> <p>Energy efficiency category A+ without</p> <p>20-28V; DC</p> <p>approx. 16 W</p> <p>approx. 1720 lm</p> <p>approx. 108 lm/W</p> <p>direct, narrow-angled beam</p> <p>neutral white, approx. 5000 K</p> <p>&gt; 80</p> <p>IP 67</p> <p>III</p> <p>switchable</p> <p>external</p> <p>aluminium, anodised, aluminium coloured anodised</p> <p>screen, clear</p> <p>approx. 0.8 kg</p> <p>built-in plug</p> <p>US-ConnectionStandard</p> <p>mounted version</p> <p>L-angle, clamp</p> <p>A=540 mm</p> <p>angle of illumination 40°</p> |
|---|---|



RSFM 4/0,05 P25-1

**illuminance**

distance: 100 cm  
**Em:** 746 lx  
**Emax:** 1270 lx  
**Emin:** 285 lx



**luminous intensity**

