



**fitted with**

**work equipment**  
**connected load**  
**Power consumption**  
**luminous flux**  
**luminous efficacy**  
**light colour**  
**color rendering index (CRI)**  
**Glare-free**  
**System of protection**  
**class of protection**  
**usage**  
**luminaire body**

**lamp cover**  
**tubular sections**

**balance of articulation joints**  
**weight (net)**  
**mains lead**

**Fastening**

LED  
 Energy efficiency category A+  
 electronic transformer  
 100-240 V; 50/60 Hz  
 approx. 24 W  
 approx. 1300 lm  
 approx. 54 lm/W  
 neutral white, approx. 4000 K  
 > 80  
 conical prismatic screen  
 IP 20  
 I  
 multi-function switch  
 sectional aluminium, anodised, aluminium coloured  
 anodised  
 acrylic clear  
 tubular aluminium section, anodized, aluminium coloured  
 anodised  
 spring  
 approx. 1.9 kg  
 approx. 3,4 m; mains plug  
 CEE 7/VII  
 screw-down flange, table clamp (accessory), wall bracket  
 (accessory)




CEE 7/VII

**illuminance**

distance: 50 cm

**Em:** 1137 lx  
**Emax:** 3053 lx  
**Emin:** 159 lx



**luminous intensity**

